



TRACTORS FOR SALE DIRECT

AUSTRALIA WIDE

S904C Tractor

01/ FEATURES

90hp 4WD with front end loader
Euro quick hitch FEL 4 in 1 bucket
1200KG Front End Loader SWL
12 Inch dual functional clutch with metal ceramic friction plate
Dedicated hydraulic pump
forced lift and down
Power steering
Flat and clear deck with side placed gear selections
Heavy duty front axle and wheel rim
Steering wheel adjustable
Seat height adjustable
rear operating levers for lift and hydraulic remote
Front loader fit shock Absorption system

02/SPECIFICATION

Engine YTO 4 cylinder water cooled
Power 90hp
Hydraulic System Two way
Hydraulic lift: forced lift and down
Flow Rate 40L/Min
Clutch 12" double action clutch
Gearbox 16F+8R shuttle shift
PTO 540/1000 rpm
Battery VARTA 12V/120A
Remotes Hydraulic remotes Dual
Cabin heater,air conditioning,video,monitor,safety light, hammer,fire extinguisher
Standard counter weighth Front:N/A Rear 172kg

03/MAIN DIMENSIONS

Overall Dimensions(LxWxH) 4280x2300x3150mm
Weight 4500kg
Wheel Base 1700/1600-1900mm
Wheel Model front 13.6-24 rear 18.4-34
Axle Base 2250mm

04/FRONT END LOADER

Max.dump height 3710mm
Max.dump bucket height 2720mm
Dump distance 740mm
Dump angle 58
Max lift load 1500kg



Specification	S404 ROPS	S504 ROPS	Y404 ROPS	Y554 ROPS	S654 ROPS	S654 CABIN	S754 ROPS	S754 CABIN	S904 ROPS	S904 CABIN	S1304 CABIN	S1604 CABIN
Engine	YTO-YD	YTO-YD	XinChai	XinChai	Quanchai	Quanchai	Quanchai	Quanchai	YTO	YTO	YTO	YTO
Power	40hp	50hp	40hp	55hp	65hp	65hp	75hp	75hp	90hp	90hp	130hp	160hp
Hydraulic System	Two way	Two way	Two way	Two way	Two way	Two way	Two way	Two way	Two way	Two way	Two way	Two way
Hydraulic Lift	draft and positon control	forced lift and down	draft and positon control	draft and positon control	draft and positon control,float	draft and positon control,float	forced lift and down	forced lift and down	forced lift and down	forced lift and down	forced lift and down	forced lift and down
Flow rate	40L/min	40L/min	40L/min	40L/min	40L/min	40L/min	40L/min	40L/min	40L/min	40L/min	50L/min	50L/min
Clutch	9" double action clutch	9" double action clutch	10" double action clutch	10" double action clutch	11" double action clutch	11" double action clutch	11" double action clutch	11" double action clutch	12" double action clutch	12" double action clutch	13" double action clutch	14" double action clutch
Gearbox	8F+8R shuttle shift	8F+8R shuttle shift	12F+12R shuttle shift	12F+12R shuttle shift	12F+12R shuttle shift	12F+12R shuttle shift	12F+12R shuttle shift	12F+12R shuttle shift	16F+8R	16F+8R	16F+8R	16F+8R
PTO	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000
Battery	VARTA 12V/80A	VARTA 12V/80A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A	VARTA 12V/120A
Max.dump height	2550mm	2550mm	2950mm	2950mm	3010mm	3010mm	3110mm	3110mm	3710mm	3710mm	3810mm	3810mm
Safe lift load	400KG	450KG	600KG	600KG	800KG	800KG	800KG	800KG	1200KG	1200KG	1500KG	1500KG
Max lift load	600KG	650KG	800KG	850KG	900KG	900KG	1000KG	1000KG	1500KG	1500KG	1700KG	1700KG
Overall dimensions(mm)	3350x1700x2500	3450x1720x2550	3600x1600x2500	3600x1700x2530	3700x1770x2800	3700x1770x2800	3800x2050x2950	3800x2050x2950	4280x2300x3150	4280x2300x3150	5150x2490x3280	5150x2490x3280
Weight	1750KG	1800KG	2150KG	2350KG	2700KG	2900KG	2900KG	3100KG	4300KG	4500KG	5100KG	5300KG
Wheel base	1400/1300-1400mm	1400/1300-1400mm	1300/1300-1500mm	1300/1300-1500mm	1400/1400-1500mm	1400/1400-1500mm	1500/1300-1600mm	1500/1300-1600mm	1700/1600-1900mm	1700/1600-1900mm	1750/1700-2300mm	1750/1700-2300mm
Wheel model	front 260/70R16 rear 320/85R24	front 10-15 rear 13.6-24	front 8.3-20 rear 12.4-28	front 10.5/80-18 rear 14.9-24	front 280/70R20 rear 380/85R24	front 280/70R20 rear 380/85R24	front 300/70R20 rear 380/85R30	front 300/70R20 rear 380/85R30	front 13.6-24 rear 18.4-34	front 13.6-24 rear 18.4-34	front 14.9-26 rear 18.4-38	front 14.9-26 rear 18.4-38
Axle Base	1820mm	1820mm	1910mm	1910mm	2040mm	2040mm	2150mm	2150mm	2250mm	2250mm	2740mm	2740mm